


WOOD STAIN

SPECIFICATION

	<p>WOOD STAIN</p>
	<p>BENEFITS :</p> <ul style="list-style-type: none"> • Dries fast; • Does not raise grain; • Reveals wood texture, allows getting deep colors; • Has antiseptic features
	<p>INGREDIENTS :</p> <p>Isopropanol, methoxypropanol, pigments</p>

Meets the requirements of ТУ BY 101040134.003-2014 and Complies with Technical Regulation and Application of Sanitary, Veterinary, and Phytosanitary Measures

DISCRIPTION AND APPLICATION :

Wood stain is an alcohol based fast drying toner.


Stain is designed to tone small wooden surfaces, furniture, stairs, tabletops and other wooden items. It can be used to renew small wear areas, minor flaws.

Does not create a surface film, but slightly penetrates the wood fiber.


Micronized pigments tone the surface creating rich and saturated colors and shades.

APPLICATION :

PREPARATIONS :



1. Clean the surface from dust and litter using a vacuum-cleaner.







2. Sand the surface with an abrasive (grit 150 – 180). Clean the surface from dust and litter using a vacuum-cleaner.

Important! Shake the wood stain container well before use.

It is recommended to test the wood stain color on a small sample of grinded wood to define the actual color.

APPLICATION METHOD :



1. Apply wood stain with brush, rags, applicator roll, disperse it or dip an item in it.

2. To make the tone shade brighter, the wood stain shall be applied 2 – 3 times. Time before the next application – 15 minutes.

3. Once dry, the wood surface shall be treated with any paint or lacquer finish.



WOOD STAIN

SPECIFICATION

TOOLS CLEANING :

Tools and dry wood stain remains can easily be cleaned with acetone.

SHELF LIFE, STORAGE AND TRANSPORTATION CONDITIONS :

12 months from the manufacture date. Keep tightly closed at temperature +5 °C to +25 °C. Keep container dry. Avoid direct sunlight and exposure to temperatures below +5 °C.

SAFETY REQUIREMENTS :

FLAMMABLE! Intended use only. Avoid contact with mucous membranes. Wear suitable rubber gloves when using the wood stain. Keep out of reach of children.

DISPOSAL :

Dispose of the preliminary water-soaked rags with wood stain remains in the tightly closed container.

