

PROTECTIVE WAX FOR HARDWOOD FLOORS

TECHNICAL INFORMATION



PROTECTIVE WAX FOR OILED AND HARDWAX-OILED HARDWOOD FLOORS

BENEFITS :

- Easy to apply;
- Creates a thin protective film with anti-slip effect;
- Gives a water- and soil-resistant effect;
- Restores initial glance

INGREDIENTS :

Natural plant waxes, aliphatic hydrocarbons

Meets TY BY 101040134.002-2014 requirements and Customs' union common sanitary-epidemiological and hygienic requirements

DESCRIPTION AND APPLICATION :

Protective wax for oiled and hardwax-oiled floors renovation is developed for regular and periodic renovation of hardwood flooring with any oil-containing finishes (natural oils, hardwax-oil, UV-oil). It is developed for regular and periodic renovation of hardwood flooring with any oil-containing finishes (natural oils, hardwax-oil, UV-oil).

Application interval:

- Living rooms: every 2 – 3 months;
- Public spaces: every 1 – 4 weeks.

If necessary, adjust application interval time.

It is recommended to use the hardwood flooring wax in children's rooms, dining rooms, kitchens, antechambers and other rooms with possible water spillage on hardwood flooring.

After installation of oiled and hardwax-oiled hardwood flooring, it is recommended to apply the wax for restoration of initial look and glance.

PERFORMANCE CHARACTERISTICS :

| | |
|----------------------|--|
| Reference: | 4270-020000 |
| Packing: | 0,75 L |
| Box pcs: | 9 pcs |
| Consumption: | 5 – 10 ml/m ² |
| Readiness condition: | Ready to use, does not need to be dissolved |
| Time to dry: | For light loads (walking) – 1 – 2 hours in a well ventilated room. Time before using floors not less than 6 hours |
| Shelf life: | 12 months |

APPLICATION :

Preliminary works: Clean the floor from sand, dust and litter using a vacuum-cleaner. Clean the floor with the hardwood flooring cleaner.

Avoid overwatering, the flooring has to be dry in 2-3 minutes after cleaning. It is recommended to provide following climatic conditions: temperature +18 °C to +25 °C, relative air humidity 40 – 60 %. It is necessary to ensure a good air flow during application and dry-out.

Important! Shake the contents well before use.

Manual application: Apply the wax to the flooring with clean cotton rags. When applied, rub the wax with clean, non-colored rags, remove wax excess to avoid heavy stains and beads. Burnish the flooring using cotton rags.

Automatic application: Apply the wax to the flooring with clean cotton rags. When applied, rub the wax using a single-head white pad buffing machine. Remove the wax excess to avoid heavy stains and beads. Burnish the flooring using the buffing machine.

FLOORING CARE :

We recommend to use cleaner for oiled and hardwax-oiled hardwood floors Coswick.



PROTECTIVE WAX FOR HARDWOOD FLOORS

COSWICK COATINGS & ADHESIVES

TECHNICAL INFORMATION

SHELF LIFE, STORAGE AND TRANSPORT CONDITIONS :

12 months. Store in a cool, dry place with a tightly closed lid. Storage and transportation temperature from + 5 ° C to + 25 ° C, protect from frost.

SAFETY REQUIREMENTS :

FLAMMABLE! For intended use only. Keep out of reach of children. Wear suitable rubber gloves when using the wax. Avoid contact with mucous membranes. If underventilated, use a respiratory protection. Do not inhale wax fumes. Avoid release to the environment. Dry film is safe and non-toxic. To prevent the spontaneous combustion, keep the wax-soaked rags in tightly closed metal containers or under water.

DISPOSAL :

Dispose of the preliminary water-soaked rags with wax remains in a tightly closed container.

