

# PROTECTIVE WAX FOR HARDWOOD FLOORS

## SPECIFICATION



### PROTECTIVE WAX FOR OILED AND HARDWAX-OILED HARDWOOD FLOORS

#### BENEFITS:

- Easy to apply;
- Creates a thin protective layer with anti-slip effect;
- Gives a water- and drift-resistant effect to surface;
- Restores original gloss

#### INGREDIENTS :

Natural plant waxes, aliphatic hydrocarbons

Meets TY BY 101040134.002-2014 requirements and Customs' union common sanitary-epidemiological and hygienic requirements

### DESCRIPTION AND APPLICATION :

Protective wax for oiled and hardwax oiled floors is a special emulsion adding water-resistant properties and renewing the surface finished with any oil coating (natural oil, hardwax oil, UV-oil etc.). Designed for regular and periodic renewal of hardwood floors finished with any oil coating (natural oil, hardwax oil, UV-oil etc.).

#### Application interval:

- Living rooms: every 2 – 3 months;
- Public areas: every 1 – 4 weeks.


Adjust application frequency if required.

It is recommended to use protective wax in children's rooms, dining rooms, kitchens, hallways and other areas with potential water spillage.


After installation of oiled and hardwax oiled hardwood floors, it is recommended to apply the wax for protection, restoration of initial look and gloss.

### APPLICATION :


#### SURFACE PREPARATION :



1. Clean the floor from sand, dust and litter with a vacuum-cleaner.



2. Clean the floor with the hardwood flooring cleaner. Avoid overwatering the floor should be dry in 2-3 minutes after cleaning.



3. It is recommended to keep air temperature between +18 °C to +25 °C, relative humidity 40 – 60 %. Good air ventilation must be ensured during the entire application and drying period.

**Important!** Mix well before use.

#### MANUAL APPLICATION :



1. Apply the wax on the floor with clean cotton tissue.



2. When applied, rub the wax with clean cotton tissue. Remove excess to avoid heavy stains and overflow.




3. Polish the floor with cotton tissue.

#### MACHINE APPLICATION :




1. Apply the wax on the floor with clean cotton tissue.



2. When applied, rub the wax with a single-disk polishing machine using white pad.



3. Remove wax excess to avoid heavy stains and overflow.



4. Polish the floor with a polishing machine.



# PROTECTIVE WAX FOR HARDWOOD FLOORS

COSWICK COATINGS &amp; ADHESIVES

---

## SPECIFICATION

---

### DRYING TIME:

Light loads (walking) – 1 – 2 hours in a well-ventilated room.  
Floor can be used in at least 6 hours.

---

### SHELF LIFE, STORAGE AND TRANSPORT CONDITIONS :

12 months. Store in a cool, dry place with a tightly closed lid. Storage and transportation temperature from + 5 ° C to + 25 ° C, protect from frost.

---

### SAFETY REQUIREMENTS :

**FLAMMABLE!** Intended use only. Keep out of reach of children. Wear rubber gloves when using. Avoid contact with mucous membranes. Respiratory protection is required in case of insufficient ventilation. Do not inhale wax vapors. Avoid release into environment. To avoid spontaneous combustion, keep the wax-soaked rags in tightly closed metal containers or under water.

---

### DISPOSAL :

Dispose of preliminary water-soaked rags with wax in a tightly closed container.

