

POLYURETHANE PRIMER COSWICK F02 PRIME

COSWICK COATINGS & ADHESIVES

SPECIFICATION

	POLYURETHANE PRIMER COSWICK F02 PRIME
	BENEFITS : • Reinforces base layer; • Does not contain water and solvents; • Increases adhesion to the floor and decreases adhesive consumption; • Can be used over underfloor heating systems
	INGREDIENTS : Modified polyurethane prepolymer
	Meets the requirements of СТБ 1263-2001

DESCRIPTION AND APPLICATION :

Polyurethane primer Coswick F02 Prime is a waterless PU-resin based compound.


Primer is designed to fortify porous mineral surfaces (concrete, cement, particle and OSB boards, calcium-sulphate and xylolite screeds) when installing hardwood flooring with any type of adhesives.

Primer is used for indoor works.


APPLICATION :



1. Remove old finishes (paint, wallpapers, dirt, etc.) if any.



2. Apply the primer with a brush, applicator roll or a spray gun over the base layer in conditions of air temperature between +5 °C and +30 °C.



3. Loose surfaces shall be primed twice within at least 2 hours.

Important! Flooring has to be glued down not later than 48 hours after priming.

TOOLS CLEANING :

Tools are easily cleaned with acetone.

SHELF LIFE, STORAGE AND TRANSPORTATION CONDITIONS :

12 months. Keep tightly closed at temperature +5 °C to +25 °C. Keep container dry. Avoid direct sunlight and exposure to temperatures below +5 °C.

SAFETY REQUIREMENTS :

For intended use only. Avoid contact with skin and mucous membranes. Keep out of reach of children.

DISPOSAL :

This material and its container must be disposed of in accordance with the requirements of legislation on environmental protection and materials disposal.